

HEAT PUMPS

ALL IN ONE DOMESTIC HEAT PUMP WATER HEATER













All In One Domestic Heat Pump Water Heater





Integral Design

compact structure and space saving.



Energy-Efficient

saving electricity 75%.



Defrost Automatically

safe use in winter.



Internet of Things

remote control and leading intelligent service.



75℃ hot water

high temperature hot water meets more customer demands.



Enamel Tank / Stainless Steel Tank resistant to rust and no furring.







Specifications

Side Air Outlet Type



Model No.	HWHSO-120	HWHSO-150
Heating Capacity (kW)	2.5	2.5
Power Input (kW)	0.6	0.6
COP	4.16	4.16
Max Power Input (kW)	3	3
Rated Current (A)	2.7	2.7
Max Current (A)	15	15
Power Supply	220V/1Ph/50Hz	220V/1Ph/50Hz
Backup Electric Heater (W)	2000	2000
Refrigerant	R134a	R134a
Net Dimension(mm)	500 x 500 x 1550	500 x 500 x 1670
Package Dimension(mm)	640 x 640 x 1720	640 x 640 x 1840
Net Weight(Kg)	89	92
Noise (dB)	48	48
Water tank volume(L)	120	150
Working temperature range (\mathcal{C})	- 7∼43	- 7∼43

Heating Testing condition: Capacity at Air 20 $^{\circ}$ C/15 $^{\circ}$ C Water Temperature from 15 $^{\circ}$ C to 55 $^{\circ}$ C.

The above data is for reference only. For more specific data, refer to the nameplate on the unit.





THERMIC HEAT TRANSFER PTY LTD 140 COURTENAY AVE, CRANBOURNE NORTH VIC 3977 , AUSTRALIA

mail@thermic-heattransfer.com.au

www.thermic-heattransfer.com.au